

MT190V-T

Концевые фрезы

	диапазон	мм
	D ≤ 12	-0,02
	D > 12	-0,03
	4 ≤ d ≤ 6	-0,008
	8 ≤ d ≤ 10	-0,009
	12 ≤ d ≤ 16	-0,011
	20 ≤ d ≤ 25	-0,013
	± 0,015	



7-ми зубые



Цилиндрический хвостовик DIN 1835A

Нормальное исполнение, радиус при вершине зуба

Обозначение	Размеры, мм					Z	Код заказа
	D	d	a	L	r		
MT190V-018Z18R07-32-L092-r05-T	18	18	32	92	0,5	7	T-TSR718-05
MT190V-018Z18R07-32-L092-r10-T	18	18	32	92	1	7	T-TSR718-10
MT190V-018Z18R07-32-L092-r15-T	18	18	32	92	1,5	7	T-TSR718-15
MT190V-018Z18R07-32-L092-r20-T	18	18	32	92	2	7	T-TSR718-20
MT190V-018Z18R07-32-L092-r25-T	18	18	32	92	2,5	7	T-TSR718-25
MT190V-018Z18R07-32-L092-r30-T	18	18	32	92	3	7	T-TSR718-30
MT190V-018Z18R07-32-L092-r40-T	18	18	32	92	4	7	T-TSR718-40
MT190V-020Z20R07-38-L104-r05-T	20	20	38	104	0,5	7	T-TSR720-05
MT190V-020Z20R07-38-L104-r10-T	20	20	38	104	1	7	T-TSR720-10
MT190V-020Z20R07-38-L104-r15-T	20	20	38	104	1,5	7	T-TSR720-15
MT190V-020Z20R07-38-L104-r20-T	20	20	38	104	2	7	T-TSR720-20
MT190V-020Z20R07-38-L104-r25-T	20	20	38	104	2,5	7	T-TSR720-25
MT190V-020Z20R07-38-L104-r30-T	20	20	38	104	3	7	T-TSR720-30
MT190V-020Z20R07-38-L104-r40-T	20	20	38	104	4	7	T-TSR720-40
MT190V-020Z20R07-38-L104-r50-T	20	20	38	104	5	7	T-TSR720-50
MT190V-020Z20R07-38-L104-r60-T	20	20	38	104	6	7	T-TSR720-60
MT190V-025Z25R07-45-L121-r05-T	25	25	45	121	0,5	7	T-TSR725-05
MT190V-025Z25R07-45-L121-r10-T	25	25	45	121	1	7	T-TSR725-10
MT190V-025Z25R07-45-L121-r15-T	25	25	45	121	1,5	7	T-TSR725-15
MT190V-025Z25R07-45-L121-r20-T	25	25	45	121	2	7	T-TSR725-20
MT190V-025Z25R07-45-L121-r25-T	25	25	45	121	2,5	7	T-TSR725-25
MT190V-025Z25R07-45-L121-r30-T	25	25	45	121	3	7	T-TSR725-30
MT190V-025Z25R07-45-L121-r40-T	25	25	45	121	4	7	T-TSR725-40
MT190V-025Z25R07-45-L121-r50-T	25	25	45	121	5	7	T-TSR725-50
MT190V-025Z25R07-45-L121-r60-T	25	25	45	121	6	7	T-TSR725-60

*Возможно изготовление фрез с цилиндрическим хвостовиком с лысками типа «Weldon» (DIN 1835B)

Код заказа для фрез с хвостовиком «Weldon» - T-TSR7...W-..., например: T-TSR720W-15

